

GAS STORAGE

PRODUCT	WARRANTY* See page 37	OUTDOOR MODELS				INDOOR MODELS			
Rheem	5 Years	A311135		A311170		441135		441170	
Stellar	10 Years		A850330		A850360				
Heavy Duty	10 Years					A63260			A62260
Storage Capacity	Litres	130	130	160	160	260	130	170	260
Recovery @ 45 °C Natural Gas	Litres	150	200	175	200	210	110	126	210
**First Hour Capacity	Litres	280	330	335	360	470	240	296	470
Hourly Gas Consumption Natural Gas	MJ	35	42	40	42	50	29	33	50
kW Output	kW	8	10.5	9	10.5	11	6.5	7.5	11
Height	A (mm)	1598	1600	1898	1900	1640	1555	1855	1660
Width	B (mm)	422	485	422	485	590	430	430	590
Depth	C (mm)	502	558	502	558	680	515	515	670
	D (mm)	988	988	1213	1213	990	N/A - Outlet on Top	N/A - Outlet on Top	990
	E (mm)	328	328	403	409	340	332	407	330
	F (mm)	298	298	298	298	295	300	300	295
	G (mm)	1478		1778		1520	1475	1775	1520
	H (mm)						75	75	100
Approx. Weight Empty	kg	68	70	79	80	106	50	59	98
Relief Valve Setting	kPa	1400	1400	1400	1400	1000	1400	1400	1000
Max. Supply Pressure		1120	1120	1120	1120	800	1120	1120	800
Water Connections (LHS)		RP 3/4" / 20	RP 3/4" / 20	RP 3/4" / 20	RP 3/4" / 20	RP 1 1/4" / 32	RP 3/4" / 20	RP 3/4" / 20	RP 1 1/4" / 32
Gas Connection		RP 1/2" / 15	RP 1/2" / 15	RP 1/2" / 15	RP 1/2" / 15	RP 1/2" / 15	RP 1/2" / 15	RP 1/2" / 15	RP 1/2" / 15

**First hour capacity is a method of comparing the capabilities of different gas water heaters. Please contact Rheem for actual hot water delivery for specific applications.

