








# WATER HEATER RANGE

## 2018

-  Electric
-  Gas
-  Boiling Water
-  Heat Pump
-  Solar

STEADY, HOT & STRONG

INSTALL A RHEEM™

[www.rheem.co.nz](http://www.rheem.co.nz)



## CONTINUOUS FLOW GAS WATER HEATERS

DOMESTIC CONTINUOUS FLOW - OUTDOOR ONLY						MJ/h
874816NFZ	CFWH	16L	355 × 187 × 520H	NATURAL GAS		126
874816LFZ	CFWH	16L	355 × 187 × 520H	ULPG		126
874820NFZ	CFWH	20L	355 × 187 × 520H	NATURAL GAS		157
874820LFZ	CFWH	20L	355 × 187 × 520H	ULPG		157
874824NFZ	CFWH	24L	355 × 187 × 520H	NATURAL GAS		188
874824LFZ	CFWH	24L	355 × 187 × 520H	ULPG		188
874627NFZ	CFWH	27L	351 × 226 × 601H	NATURAL GAS		205
874627LPZ	CFWH	27L	351 × 226 × 601H	ULPG		205
DOMESTIC CONTINUOUS FLOW - INDOOR ONLY						MJ/h
864627NFZ	CFWH	27L	331 × 240 × 650H	NATURAL GAS*		205
864627LPZ	CFWH	27L	331 × 240 × 650H	ULPG*		205
COMMERCIAL CONTINUOUS FLOW MODELS					MAX TEMP	MJ/h
872627NFZ	CFWH	27L	351 × 226 × 601H	NG OUTDOOR	82°	205
872627LPZ	CFWH	27L	351 × 226 × 601H	ULPG OUTDOOR	82°	205
862627NFZ	CFWH	27L	351 × 215 × 601H	NG INDOOR	82°	205
862627LPZ	CFWH	27L	351 × 215 × 601H	ULPG INDOOR	82°	205

Warranty: 10yr heat exchanger, 3yr parts and labour

# CONTINUOUS FLOW GAS WATER HEATERS

## ACCESSORIES

A299850	STANDARD CONTROLLER & 20M CABLE	KITCHEN
A299851	STANDARD CONTROLLER & 20M CABLE	BATHROOM 1
A299852	STANDARD CONTROLLER & 20M CABLE	BATHROOM 2
A299861	DELUXE CONTROLLER & 20M CABLE	KITCHEN
A299862	DELUXE CONTROLLER & 20M CABLE	BATHROOM 1
A299863	DELUXE CONTROLLER & 20M CABLE	BATHROOM 2
290141	EZ LINK® KIT TO INCREASE SUPPLY	
318994	RECESS BOX COMPLETE KIT (NEW COLOUR)	16L, 20L & 24L MODELS
320316	RECESS BOX COMPLETE KIT (NEW COLOUR)	27L OUTDOOR MODEL
320117	PIPE COVER (NEW COLOUR)	16L, 20L & 24L MODELS
320116	PIPE COVER (NEW COLOUR)	27L MODELS

## FLUE KITS FOR 27L INDOOR MODEL

318278	FLUE KIT SIDE EXIT - HORIZONTAL	1320MM - MAX LENGTH
318279	FLUE KIT REAR EXIT - HORIZONTAL	720MM - MAX LENGTH
318280	FLUE KIT - VERTICAL	1200MM - MAX LENGTH

## FLUE ACCESSORIES FOR 27L INDOOR MODEL

295116	FLUE CFWH INT 3/5 HORIZONTAL TERMINAL
295117	FLUE CFWH INT 3/5 VERTICAL TERMINAL
295118	FLUE CFWH INT 3/5 90° BEND
295119	FLUE CFWH INT 3/5 45° BEND
295120	FLUE CFWH INT 3/5 CONDENSATE DRAIN
295122	FLUE CFWH INT 3/5 STRAIGHT LENGTH 900MM
295123	FLUE CFWH INT 3/5 FEMALE/FEMALE ADAPTOR
295124	FLUE CFWH INT 3/5 MALE/MALE ADAPTOR
295125	FLUE CFWH INT 3/5 TRIM RING
295126	FLUE CFWH INT 3/5 STRAIGHT LENGTH 300MM
295127	FLUE CFWH INT 3/5 ADJUSTABLE LENGTH 560 - 890MM
295129	FLUE CFWH INT 3/5 BRACKET
295139	FLUE CFWH INT 3/5 CONDENSATE TRAP

\*Indoor continuous flow gas water heaters must be installed using a certified Rheem flue system.  
Always check with local authorities that the installation complies with all regulations applicable in your area.

FREE PHONE 0800 657 336

## RAISED AND DUAL INLETS

Rheem have raised the inlets on their Mains and Low Pressure Vitreous Enamel (VE) cylinders to 120mm. An additional inlet socket has also been added to Mains Pressure VE single element cylinders (45L - 300L).

### MAINS PRESSURE ELECTRIC - VITREOUS ENAMEL (VE)

MP DOMESTIC INDOOR ELECTRIC STORAGE (VE)				
312 025 19	MPVE	25L	405 × 380H	2kW
312 045 15	MPVE	45L	490 × 525H	3kW
312 090 15	MPVE	90L	490 × 925H	3kW
312 135 13	MPVE	135L	490 × 1325H	2kW
312 135 15	MPVE	135L	490 × 1325H	3kW
322 135 15	MPVE	135L	580 × 935H	3kW
312 180 13	MPVE	180L	490 × 1710H	2kW
312 180 15	MPVE	180L	490 × 1710H	3kW
322 180 15	MPVE	180L	580 × 1165H	3kW
312 180 25	MPVE	180L	490 × 1710H	2 × 3kW twin element (non-simultaneous)
312 250 15	MPVE	250L	580 × 1555H	3kW
312 250 25	MPVE	250L	580 × 1555H	2 × 3kW twin element (non-simultaneous)
312 300 15	MPVE	300L	580 × 1815H	3kW
312 300 33	MPVE	300L	580 × 1815H	2 × 3kW dual element (simultaneous)
312 300 55	MPVE	300L	580 × 1815H	2 × 5kW dual element (simultaneous)
MP OPTIMA INDOOR OR OUTDOOR ELECTRIC STORAGE (VE)				
913 180 15	OPTIMA	180L	490 X 1720H	3kW
913 300 25	OPTIMA	300L	580 X 1820H	2 × 3kW twin element (non-simultaneous)
ACCESSORIES				
319026	REPLACEMENT ELEMENT	2kW INCOLOY 800 (bolt-on) 25L only		
320162	REPLACEMENT ELEMENT	2kW COPPER PLATED (screw-in)		
320163	REPLACEMENT ELEMENT	3kW COPPER PLATED (screw-in)		
320165	REPLACEMENT ELEMENT	5kW INCOLOY 800 (screw-in)		
315825	REPLACEMENT THERMOSTAT	STANDARD MAINS PRESSURE		
317023	REPLACEMENT THERMOSTAT	OPTIMA MAINS PRESSURE		
11077	REPLACEMENT THERMOSTAT	STANDARD & OPTIMA (top element)		
10975	REPLACEMENT THERMOSTAT	25L & 45L MODELS		

Warranty: 10yr tank, 5yr tank labour, 1yr parts and labour

Warranty Optima: 12yr tank, 5yr tank labour, 3yr parts and labour

## MAINS PRESSURE ELECTRIC — STAINLESS STEEL

MP DOMESTIC INDOOR & OUTDOOR ELECTRIC STORAGE (SS)						
325 135 03 - 0	MPSS	135L	490 × 1350H	2kW		
325 135 05 - 0	MPSS	135L	490 × 1350H	3kW		
325 180 03 - 0	MPSS	180L	490 × 1770H	2kW		
325 180 05 - 0	MPSS	180L	490 × 1770H	3kW		
325 250 05 - 0A	MPSS	250L	580 × 1595H	3kW		
325 300 05 - 0A	MPSS	300L	580 × 1890H	3kW		
ACCESSORIES						
318241	KITSET (element/thermostat) SOLAR/HP 2kW 180L (325180)					
318242	KITSET (element/thermostat) SOLAR/HP 2kW 250 & 300L (325250 & 325300)					
318243	KITSET (element/thermostat) SOLAR/HP 3kW 250 & 300L (325250 & 325300)					
319026	REPLACEMENT ELEMENT 2kW INCOLOY 800 (bolt-on) bottom element (135L & 180L)					
319005	REPLACEMENT ELEMENT 3kW INCOLOY 800 (bolt-on) (135L–300L)					
09002	REPLACEMENT THERMOSTAT (top element)					
315825	REPLACEMENT THERMOSTAT (bottom element)					

Warranty: 10yr tank, 3yr tank labour, 1yr parts and labour

## MAINS PRESSURE ELECTRIC — STAINLESS STEEL COIL

MP DOMESTIC INDOOR ELECTRIC STORAGE (SS) COIL						
356 250 15ML	MPSS	250L	560 × 1725H	3kW	MID COIL LHD	(LEFT)
356 250 15MR	MPSS	250L	560 × 1725H	3kW	MID COIL RHD	(RIGHT)
356 250 15LL	MPSS	250L	560 × 1725H	3kW	LOWER COIL LHD	(LEFT)
356 250 15LR	MPSS	250L	560 × 1725H	3kW	LOWER COIL RHD	(RIGHT)
356 250 15DL	MPSS	250L	560 × 1725H	3kW	DUAL COIL LHD	(LEFT)
356 300 15ML	MPSS	300L	560 × 2045H	3kW	MID COIL LHD	(LEFT)
356 300 15MR	MPSS	300L	560 × 2045H	3kW	MID COIL RHD	(RIGHT)
356 300 15LL	MPSS	300L	560 × 2045H	3kW	LOWER COIL LHD	(LEFT)
356 300 15LR	MPSS	300L	560 × 2045H	3kW	LOWER COIL RHD	(RIGHT)
356 300 15DL	MPSS	300L	560 × 2045H	3kW	DUAL COIL LHD	(LEFT)
ACCESSORIES						
417026	ELEMENT & THERMOSTAT KIT			3kW		
319101	REPLACEMENT ELEMENT			3kW	INCOLOY 800 (screw-in)	
319127	TITANIUM ELEMENT KIT*			2kW	(SCREW-IN)	
319128	TITANIUM ELEMENT KIT*			2kW	(SCREW-IN)	LOW WATT DENSITY
319129	TITANIUM ELEMENT KIT*			3kW	(SCREW-IN)	
319130	TITANIUM ELEMENT KIT*			3kW	(SCREW-IN)	LOW WATT DENSITY
09002	REPLACEMENT THERMOSTAT					

\*Titanium is ideal for harsher water conditions

Warranty: 10yr tank, 3yr tank labour, 1yr parts and labour

## MAINS PRESSURE GAS STORAGE

MP GAS STORAGE – INDOOR ONLY - NATURAL GAS				
441 135 NO	MP GAS	130L	430 × 1555H NG INT – FAST RECOVERY	
441 170 NO	MP GAS	160L	430 × 1855H NG INT – FAST RECOVERY	
MP STELLAR – GAS STORAGE - OUTDOOR ONLY - NATURAL GAS				
850330NOZ	MP GAS	130L	485 X 1600H NG EXT – HIGH EFFICIENCY	
850360NOZ	MP GAS	160L	485 X 1900H NG EXT – HIGH EFFICIENCY	

Warranty: 10yr tank, 5yr tank labour, 1yr parts and labour

## LOW PRESSURE ELECTRIC — VITREOUS ENAMEL (VE)

LP DOMESTIC INDOOR ELECTRIC STORAGE (VE)					
148 090 13T	LPVE	90L	490 × 915H	2kW	TRIPLE INLET
148 090 15T	LPVE	90L	490 × 915H	3kW	TRIPLE INLET
148 135 13T	LPVE	135L	490 × 1315H	2kW	TRIPLE INLET
148 135 15T	LPVE	135L	490 × 1315H	3kW	TRIPLE INLET
148 180 13T	LPVE	180L	490 × 1710H	2kW	TRIPLE INLET
148 180 15T	LPVE	180L	490 × 1710H	3kW	TRIPLE INLET
158 135 13T	LPVE	135L	580 × 880H	2kW	TRIPLE INLET
158 135 15T	LPVE	135L	580 × 880H	3kW	TRIPLE INLET
158 180 13T	LPVE	180L	580 × 1135H	2kW	TRIPLE INLET
158 180 15T	LPVE	180L	580 × 1135H	3kW	TRIPLE INLET
158 270 15T	LPVE	270L	580 × 1640H	3kW	TRIPLE INLET
ACCESSORIES					
319026	REPLACEMENT ELEMENT			2kW	INCOLOY 800 (bolt-on)
319005	REPLACEMENT ELEMENT			3kW	INCOLOY 800 (bolt-on)
315825	REPLACEMENT THERMOSTAT				

Warranty: 10yr tank, 5yr tank labour, 1yr parts and labour

## LOW PRESSURE ELECTRIC — COPPER

LP DOMESTIC INDOOR ELECTRIC STORAGE (COPPER)					
149 040 13	LP	40L	460 × 490H	2kW	BOTTOM INLET
14T 090 13	LP	90L	510 × 785H	2kW	TRIPLE INLET
14T 110 13	LP	110L	510 × 950H	2kW	TRIPLE INLET
12T 135 13	LP	135L	610 × 800H	2kW	TRIPLE INLET
14T 135 13	LP	135L	560 × 955H	2kW	TRIPLE INLET
16T 135 13	LP	135L	510 × 1140H	2kW	TRIPLE INLET

## LOW PRESSURE ELECTRIC — COPPER

LP DOMESTIC INDOOR ELECTRIC STORAGE (COPPER) CONT'D					
18T 135 13	LP	135L	460 × 1465H	2kW	TRIPLE INLET
54T 135 13	LP	135L	540 × 1030H	2kW	TRIPLE INLET
12T 180 13	LP	180L	610 × 1020H	2kW	TRIPLE INLET
12T 180 15	LP	180L	610 × 1020H	3kW	TRIPLE INLET
14T 180 13	LP	180L	560 × 1220H	2kW	TRIPLE INLET
14T 180 15	LP	180L	560 × 1220H	3kW	TRIPLE INLET
54T 180 13	LP	180L	540 × 1355H	2kW	TRIPLE INLET
54T 180 15	LP	180L	540 × 1355H	3kW	TRIPLE INLET
16T 180 13	LP	180L	510 × 1510H	2kW	TRIPLE INLET
16T 180 15	LP	180L	510 × 1510H	3kW	TRIPLE INLET
149 225 15	LP	225L	610 × 1250H	3kW	BOTTOM INLET
169 225 15	LP	225L	560 × 1510H	3kW	BOTTOM INLET
149 270 15	LP	270L	610 × 1470H	3kW	BOTTOM INLET
149 270 25	LP	270L	610 × 1470H	2 × 3kW	TWIN ELEMENT (simultaneous)
169 270 15	LP	270L	560 × 1800H	3kW	BOTTOM INLET
169 270 25	LP	270L	560 × 1800H	2 × 3kW	TWIN ELEMENT (simultaneous)
149 350 25	LP	350L	655 × 1595H	2 × 3kW	TWIN ELEMENT (simultaneous)
LP WETBACK (COPPER)					
145 135 13	LP	135L	560 × 955H	BCRL	2kW
165 135 13	LP	135L	510 × 1140H	BCRL	2kW
185 135 13	LP	135L	460 × 1465H	BCRL	2kW
125 180 15	LP	180L	610 × 1020H	BCRL	3kW
143 180 15	LP	180L	560 × 1220H	RHSC	3kW
144 180 15	LP	180L	560 × 1220H	LHSC	3kW
145 180 15	LP	180L	560 × 1220H	BCRL	3kW
545 180 13	LP	180L	540 × 1355H	BCRL	2kW
545 180 15	LP	180L	540 × 1355H	BCRL	3kW
165 180 15	LP	180L	510 × 1510H	BCRL	3kW
145 225 15	LP	225L	610 × 1250H	BCRL	3kW
165 225 15	LP	225L	560 × 1520H	BCRL	3kW
145 270 15	LP	270L	610 × 1465H	BCRL	3kW
165 270 15	LP	270L	560 × 1800H	BCRL	3kW
LP TANK UNITS (COPPER)					
T49 135 13	LP	135L	560 × 1260H	2kW	
T49 180 15	LP	180L	560 × 1530H	3kW	

## LOW PRESSURE ELECTRIC — COPPER

### LP UNDERBENCH UNITS

199 015 13	LP	15L	365 × 370H	UNDERBENCH	2kW	TOP INLET & OUTLET
199 025 13	LP	25L	365 × 525H	UNDERBENCH	2kW	TOP INLET & OUTLET
199 040 13	LP	40L	460 × 490H	UNDERBENCH	2kW	TOP INLET & OUTLET

### LP COPPER, TANK & UNDERBENCH ACCESSORIES

320162	REPLACEMENT ELEMENT	2kW	COPPER PLATED (screw-in)
319100	REPLACEMENT ELEMENT	2kW	INCOLOY 800 (bolt-on) (15L–40L)
320163	REPLACEMENT ELEMENT	3kW	COPPER PLATED (screw-in)
319127	TITANIUM ELEMENT KIT*	2kW	(SCREW-IN)
319128	TITANIUM ELEMENT KIT*	2kW	(SCREW-IN) LOW WATT DENSITY
319129	TITANIUM ELEMENT KIT*	3kW	(SCREW-IN)
319130	TITANIUM ELEMENT KIT*	3kW	(SCREW-IN) LOW WATT DENSITY
315825	REPLACEMENT THERMOSTAT		
317312	REPLACEMENT THERMOSTAT (WETBACK)		
10975	REPLACEMENT THERMOSTAT (15L–40L)		

### LP DAIRY ELECTRIC STORAGE (COPPER)

109 250 1G	LP	250L	760 × 1235H	DAIRY	3kW/3kW
109 350 1G	LP	350L	760 × 1530H	DAIRY	3kW/3kW
109 450 1G	LP	450L	760 × 1835H	DAIRY	3kW/3kW
109 600 1G	LP	600L	840 × 1885H	DAIRY	3kW/3kW

### LP DAIRY ACCESSORIES

319105	REPLACEMENT ELEMENT	3kW/3kW	INCOLOY 800 (screw-in)
315948	REPLACEMENT THERMOSTAT	(DAIRY)	

### LP HEAVY HEAD

146 180 15	LP	180L	560 × 1220H	HHD	3kW
166 180 15	LP	180L	510 × 1510H	HHD	3kW

### LP HEAVY HEAD ACCESSORIES

320163	REPLACEMENT ELEMENT	3kW	COPPER PLATED (screw-in)
315825	REPLACEMENT THERMOSTAT		

Warranty: 5yr tank, 1yr tank labour, 1yr parts and labour

FREE PHONE 0800 657 336



## MAINS PRESSURE - HEAT PUMP

HEAT PUMP				
A55131007	HDI-310 HD	INTEGRATED HEAT PUMP	310L	3.6kW (2 MODULES)
A55132507	MPI-325 HD	INTEGRATED HEAT PUMP	325L	3.6kW (2 MODULES)
HEAT PUMP ACCESSORIES				
319111	REPLACEMENT ELEMENT		3.6kW	OFFSET (bolt-on)
052063	REPLACEMENT THERMOSTAT		310L MODEL	
052073	REPLACEMENT THERMOSTAT		325L MODEL	

Warranty: 5yr tank, 3yr tank labour, 1yr parts and labour, 2yr sealed system

## MAINS PRESSURE - SOLAR

PREMIER SOLAR LOLINE SYSTEM		* Flue Kit not Included
A591270/2T	2 COLLECTORS & 270L TANK ELECTRIC BOOST*	
A591270/3T	3 COLLECTORS & 270L TANK ELECTRIC BOOST*	
A591270/2TGL	2 COLLECTORS & 270L TANK GAS BOOST ULPG –	OUTDOOR ONLY
A591270/2TGN	2 COLLECTORS & 270L TANK GAS BOOST NG –	OUTDOOR ONLY
A591270/3TGL	3 COLLECTORS & 270L TANK GAS BOOST ULPG –	OUTDOOR ONLY
A591270/3TGN	3 COLLECTORS & 270L TANK GAS BOOST NG –	OUTDOOR ONLY
A591270/2TGL/ID	2 COLLECTORS & 270L TANK GAS BOOST ULPG –	INDOOR ONLY
A591270/2TGN/ID	2 COLLECTORS & 270L TANK GAS BOOST NG –	INDOOR ONLY
A591270/3TGL/ID	3 COLLECTORS & 270L TANK GAS BOOST ULPG –	INDOOR ONLY
A591270/3TGN/ID	3 COLLECTORS & 270L TANK GAS BOOST NG –	INDOOR ONLY
SOLAR TANKS – INDOOR & OUTDOOR		
A51127007	270L SOLAR TANK WITH 3.6kW BOOSTER	640 × 1395H
A51134007	325L SOLAR TANK WITH 3.6kW BOOSTER	640 × 1640H
A51143007	410L SOLAR TANK WITH 3.6kW BOOSTER	690 × 1840H
ACCESSORIES		
AC2000000K	PREMIER LOLINE 1C COLLECTOR - EXTRA PANEL KIT	
319000	STAND PITCH ADJUSTMENT KIT - 2 COLLECTORS 13°	
319001	STAND PITCH ADJUSTMENT KIT - 3 COLLECTORS 13°	
319002	STAND PITCH ADJUSTMENT KIT - 2 COLLECTORS 25°	
319003	STAND PITCH ADJUSTMENT KIT - 3 COLLECTORS 25°	
318278	FLUE KIT SIDE EXIT - HORIZONTAL (INDOOR MODEL ONLY)	
318279	FLUE KIT REAR EXIT - HORIZONTAL (INDOOR MODEL ONLY)	
318280	FLUE KIT - VERTICAL (INDOOR MODEL ONLY)	

Roof space required: 2 Collectors 2.4m x 2m, 3 collectors 3.6m x 2m

## ON-TAP BOILING WATER

ON-TAP FILTERED, BOILING AND COLD DRINKING WATER				
743003F	AQUA	3L UNDERBENCH BW UNIT	175 × 460 × 405H	1.5kW
743005F	AQUA	5L UNDERBENCH BW UNIT	175 × 460 × 405H	1.8kW
743103F	AZURE	3L UNDERBENCH BW UNIT	175 × 460 × 405H	1.5kW
743105F	AZURE	5L UNDERBENCH BW UNIT	175 × 460 × 405H	1.8kW
CHILLER UNIT				
318844	PUSH-THRU CHILLED WATER UNIT (OPTIONAL)			
ACCESSORIES				
317067	REPLACEMENT FILTER (5 micron)			
317453	ON-TAP AQUA SINK-FREE & EXTENSION KIT			
319042	ON-TAP AZURE SINK-FREE & EXTENSION KIT			
319047	ON-TAP AZURE COMBINED BASE SINK-FREE & EXTENSION KIT			
317346	REPLACEMENT ELEMENT 1.5kW INCOLOY 800			
317164	REPLACEMENT ELEMENT 1.8kW INCOLOY 800			

On-Tap warranty: 5yr tank, 2yr tank labour, 2yr parts/labour

AZURE™

AQUA™



## ZIP® BOILING WATER UNITS

ZIP® - MANUAL OPERATION - INSTALLED OVERSINK				
832 045 14	ZIP 4.5L	340W × 430H × 180D	MANUAL	2.4kW
832 070 14	ZIP 7L	340W × 515H × 180D	MANUAL	2.4kW
832 150 14	ZIP 15L	490W × 615H × 180D	MANUAL	2.4kW
832 230 14	ZIP 23L	490W × 615H × 235D	MANUAL	2.4kW
832 350 14	ZIP 34L	490W × 615H × 325D	MANUAL	2.4kW
ZIP® ACCESSORIES				
315881	REPLACEMENT ELEMENT 2.4kW INCOLOY 800			
316016	REPLACEMENT THERMODISC AND O-RING			

ZIP® warranty: 5yr tank, 1yr tank labour, 1yr parts and labour

# LAZER® BOILING WATER UNITS

LAZER® OFFICE					Initial Draw Off of 200ml Cups
70103W-NZ	LAZER 3L	283W × 435H × 206D	1.8kW	WHITE	20
70103S-NZ	LAZER 3L	283W × 435H × 206D	1.8kW	S/STEEL	20
70105W-NZ	LAZER 5L	334W × 465H × 239D	2.4kW	WHITE	35
70105S-NZ	LAZER 5L	334W × 465H × 239D	2.4kW	S/STEEL	35
LAZER® ECO					
70303W-NZ	LAZER 3L	283W × 435H × 158D	1.8kW	WHITE	20
70305W-NZ	LAZER 5L	334W × 465H × 191D	2.4kW	WHITE	35
70307W-NZ	LAZER 7.5L	334W × 515H × 191D	2.4kW	WHITE	50
LAZER® COMMERCIAL					
70207W-NZ	LAZER 7.5L	334W × 515H × 191D	2.4kW	WHITE	50
70207S-NZ	LAZER 7.5L	334W × 515H × 191D	2.4kW	S/STEEL	50
70210W-NZ	LAZER 10L	334W × 615H × 191D	2.4kW	WHITE	60
70210S-NZ	LAZER 10L	334W × 615H × 191D	2.4kW	S/STEEL	60
70215W-NZ	LAZER 15L	334W × 515H × 299D	2.4kW	WHITE	90
70215S-NZ	LAZER 15L	334W × 515H × 299D	2.4kW	S/STEEL	90
70225W-NZ	LAZER 25L	334W × 720H × 299D	3.6kW	WHITE	150
70225S-NZ	LAZER 25L	334W × 720H × 299D	3.6kW	S/STEEL	150
70240W-NZ	LAZER 40L	490W × 615H × 340D	4.6kW	WHITE	250
70240S-NZ	LAZER 40L	490W × 615H × 340D	4.6kW	S/STEEL	250
LAZER® ACCESSORIES					
317327	REMOTE FILTER KIT (5 micron)				
381961	RETROFIT MOUNTING BRACKET (3L LAZER® ECO)				
381962	RETROFIT MOUNTING BRACKET (5L LAZER® ECO)				
317164	REPLACEMENT ELEMENT	1.8kW	240V	INCOLOY 800	
315881	REPLACEMENT ELEMENT	2.4kW	240V	INCOLOY 800	
315883	REPLACEMENT ELEMENT	3.6kW	240V	INCOLOY 800	
315884	REPLACEMENT ELEMENT	4.6kW	240V	INCOLOY 800	LONG
319007	REPLACEMENT ELEMENT	3.6kW	240V	INCOLOY 800	L-SHAPE
319068	SAFETY TAP FOR LAZER® COMMERCIAL				
319069	SAFETY TAP FOR LAZER® ECO				

LAZER® warranty: 5yr tank, 2yr tank labour, 2yr parts/labour

## COMMERCIAL & INDUSTRIAL - STORAGE

### COMMERCIAL - HEAT PUMPS (3 PHASE)

95302200D/A	HP EXT/NON-DUCTED	(16kW top discharge)*	OUTDOOR
95202200D/A	HP INT/DUCTED	(16kW top discharge)*	INDOOR
95302200D/H	HP EXT/NON-DUCTED	(16kW side discharge)*	OUTDOOR
95202200D/H	HP INT/DUCTED	(16kW side discharge)*	INDOOR

\*Requires 1 controller (#052140) with up to 6 heat pumps when manifolded in the same plumbing system

### COMMERCIAL - HEAT PUMP ACCESSORIES

052140	HEAT PUMP CONTROLLER
366084	CENTRIFUGAL PUMP GRUNDFOS MODEL CM3-2 (1 per 3 Phase Heat Pump)

### COMMERCIAL MP HEAVY DUTY ELECTRIC STORAGE - OUTDOOR OR INDOOR

A613050/3.6	MP ELECTRIC	50L	435 × 665H	3 × 3.6kW
A613050	MP ELECTRIC	50L	435 × 665H	3 × 4.8kW
A613315/3.6	MP ELECTRIC	315L	650 × 1695H	3 × 3.6kW
A613315	MP ELECTRIC	315L	650 × 1695H	3 × 4.8kW
A613315/6K	MP ELECTRIC	315L	650 × 1695H	3 × 6kW
A616315/3.6	MP ELECTRIC	315L	650 × 1695H	6 × 3.6kW
A616315	MP ELECTRIC	315L	650 × 1695H	6 × 4.8kW
A616315/6K	MP ELECTRIC	315L	650 × 1695H	6 × 6kW

### COMMERCIAL MP HEAVY DUTY GAS STORAGE - INDOOR & OUTDOOR

					MJ/h
620260NO	MP GAS	260L	590W × 670D × 1660H	INDOOR NG	50
621265NO	MP GAS	265L	610W × 750D × 1795H	INDOOR NG	110
621265LO	MP GAS	265L	610W × 750D × 1795H	INDOOR ULPG	110
621275NO	MP GAS	275L	640W × 780D × 1895H	INDOOR NG	200
621275LO	MP GAS	275L	640W × 780D × 1895H	INDOOR ULPG	200
630260NO	MP GAS	260L	590W × 680D × 1640H	OUTDOOR NG	50
631265NO	MP GAS	265L	610W × 710D × 1835H	OUTDOOR NG	110
631265LO	MP GAS	265L	610W × 710D × 1835H	OUTDOOR ULPG	110
631275NO	MP GAS	275L	640W × 780D × 1865H	OUTDOOR NG	200
631275LO	MP GAS	275L	640W × 780D × 1865H	OUTDOOR ULPG	200

### COMMERCIAL STORAGE TANKS - OUTDOOR OR INDOOR (ALL MODELS)

A610340	STORAGE	325L	650 × 1695H	HEAVY DUTY	3 × 50mm CONNECTIONS
A610430	STORAGE	410L	690 × 1875H	HEAVY DUTY	3 × 50mm CONNECTIONS
RT1000N9AL	STORAGE	920L	1000 × 2200H	316 S/S	8 × 50mm CONNECTIONS^
RT2000N9AL	STORAGE	2055L	1300 × 2565H	316 S/S	8 × 50mm CONNECTIONS^
RT3000N9AL	STORAGE	2960L	1450 × 2845H	316 S/S	8 × 50mm CONNECTIONS^

## COMMERCIAL STORAGE TANKS - OUTDOOR OR INDOOR (ALL MODELS)

RT4000N9AL	STORAGE	3820L	1600 × 2918H 316 S/S	8 × 50mm CONNECTIONS <sup>^</sup>
RT5000N9AL	STORAGE	5180L	1800 × 3128H 316 S/S	8 × 50mm CONNECTIONS <sup>^</sup>

<sup>^</sup>Includes 4 x sensor probe pockets

## COMMERCIAL & INDUSTRIAL - TANKPAK®

Rheem Tankpak® systems provide flexibility around installation, size, delivery and storage while combining the benefits of mains pressure with continuous flow gas water heating (CFWH). With the ability to combine up to 18 CFWH units and 1–4 storage tanks, talk to our Commercial team for a solution to your commercial water heating requirements.



**TANKPAK® CONCEPT** (FRAME NOT INCLUDED)  
COMPONENTS SUPPLIED LOOSE (1–10 UNITS)



**TANKPAK® SERIES 2**  
PRE-PLUMBED ON A FRAME (2–18 UNITS)

## COMMERCIAL - TANKPAK® SERIES 2

PRE-PLUMBED ON A FRAME INCL. PUMP & CONTROLLER		RECOVERY	DEL 1ST HR*	MJ/h
S2TPE02/ TPI02	2 × 27L CFWH EXT- 1 × TANK-1	1645**	1866L	410
S2TPE03/ TPI03	3 × 27L CFWH EXT- 1 × TANK-1	2470**	2669L	615
S2TPE04/ TPI04	4 × 27L CFWH EXT- 1 × TANK-1	3290**	3473L	820
S2TPE05/ TPI05	5 × 27L CFWH EXT- 1 × TANK-1	4115**	4525L	1025
S2TPE06/ TPI06	6 × 27L CFWH EXT- 1 × TANK-1	4935**	5348L	1230
S2TPE07/ TPI07	7 × 27L CFWH EXT- 2 × TANK-1	5760**	6170L	1435
S2TPE08/ TPI08	8 × 27L CFWH EXT- 2 × TANK-1	6580**	7400L	1640
S2TPE09/ TPI09	9 × 27L CFWH EXT- 2 × TANK-1	7405**	8225L	1845
S2TPE10/ TPI010	10 × 27L CFWH EXT-2 × TANK-1	8225**	9045L	2050
S2TPE12/ TPI012	12 × 27L CFWH EXT-2 × TANK-1	8875**	10695L	2460
S2TPE14/ TPI014	14 × 27L CFWH EXT-2 × TANK-1	11520**	12750L	2870
S2TPE16/ TPI016	16 × 27L CFWH EXT-2 × TANK-1	13165**	14395L	3280
S2TPE18/ TPI018	18 × 27L CFWH EXT-2 × TANK-1	14180**	16040L	3690

E=EXTERNAL I=INTERNAL \* @ 50°C RISE WITH NOMINAL 430L TANK \*\* @ 50°C RISE L/HR

# RAYPAK GAS WATER & POOL HEATERS

## RAYPAK WATER HEATERS (ULPG MODELS AVAILABLE - PLEASE SPECIFY)

B0200 *CO	WATER HEATER		OUTDOOR
B0200 *CO/ID	WATER HEATER		INDOOR
B0280 *CO	WATER HEATER	277 MJ/h 62kW	OUTDOOR
B0280 *CO/ID	WATER HEATER	277 MJ/h 62kW	INDOOR
B0350 *CO	WATER HEATER	343 MJ/h 76kW	OUTDOOR
B0350 *CO/ID	WATER HEATER	343 MJ/h 76kW	INDOOR
B0430 *CO	WATER HEATER	420 MJ/h 94kW	OUTDOOR
B0430 *CO/ID	WATER HEATER	420 MJ/h 94kW	INDOOR

MODELS ALSO AVAILABLE FROM 507 MJ/H (110kW) TO 4224 MJ/H (kW) - CALL RHEEM

## WATER HEATING & POOL HEATER OPTIONS

MODULATING BURNERS, CUPRO – NICKEL HEAT EXCHANGERS & HIGH WIND TOPS

## POOL HEATERS (ULPG MODELS AVAILABLE - PLEASE SPECIFY)

P0131 *CONZ	SPARTAN POOL HEATER 24kW		OUTDOOR ONLY
P0127 *NO NZ/OD	POOL HEATER	110 MJ/h 24kW	OUTDOOR
P0127 *NO NZ/ID	POOL HEATER	110 MJ/h 24kW	INDOOR
P0167 *NO NZ/OD	POOL HEATER	164 MJ/h 36kW	OUTDOOR
P0167 *NO NZ/ID	POOL HEATER	164 MJ/h 36kW	INDOOR
P0200 *NO NZ	POOL HEATER	196 MJ/h 44kW	OUTDOOR (COMPLETE)
P0200 *NO NZ/ID	POOL HEATER	196 MJ/h 44kW	INDOOR (WITH HOOD)
P0280 *NO NZ	POOL HEATER	278 MJ/h 62kW	OUTDOOR (COMPLETE)
P0280 *NO NZ/ID	POOL HEATER	278 MJ/h 62kW	INDOOR (WITH HOOD)
P0350 *NO NZ	POOL HEATER	343 MJ/h 76kW	OUTDOOR (COMPLETE)
P0350 *NO NZ/ID	POOL HEATER	343 MJ/h 76kW	INDOOR (WITH HOOD)
P0430 *NO NZ	POOL HEATER	427 MJ/h 94kW	OUTDOOR (COMPLETE)
P0430 *NO NZ/ID	POOL HEATER	427 MJ/h 94kW	INDOOR (WITH HOOD)

MODELS FROM 507 MJ (110KW) TO 4224 MJ (960KW) IN NATURAL GAS & SOME ULPG MODELS - CALL RHEEM

## RAYPAK PREMIUM COMMERCIAL POOL HEATERS

PC0280 *NO NZ	POOL HEATER	278 MJ/h 62kW	OUTDOOR (COMPLETE)
PC0280 *NO NZ/ID	POOL HEATER	278 MJ/h 62kW	INDOOR (WITH HOOD)
PC0430 *NO NZ	POOL HEATER	427 MJ/h 94kW	OUTDOOR (COMPLETE)
PC0430 *NO NZ/ID	POOL HEATER	427 MJ/h 94kW	INDOOR (WITH HOOD)

NB: substitute \* with N - Natural Gas or P - ULPG models

## SPECIFICATION GUIDES

ALL INFORMATION IS CURRENT AT TIME OF PUBLICATION (JULY 2018) BUT MAY CHANGE WITHOUT NOTICE.

### ELECTRIC (@ 230V)

kW	RECOVERY ON A 50°C RISE	AMPS
2.0kW	34 LITRES PER HR (Domestic)	8.7
2.4kW	40 LITRES PER HR (Domestic)	10.4
3.0kW	51 LITRES PER HR (Domestic)	13.1
3.6kW	62 LITRES PER HR	15.7
4.8kW	82 LITRES PER HR (Commercial)	20.0
5.0kW	85 LITRES PER HR (Domestic)	21.8
6.0kW	103 LITRES PER HR (Commercial)	26.1
2 × 3.0kW	103 LITRES PER HR	26.2
2 × 5.0kW	171 LITRES PER HR	43.6

### NATURAL GAS CONSUMPTION & RECOVERY RATES

	MP INDOOR		STELLAR MP OUTDOOR	
MODEL	441	441	850	850
STORAGE CAPACITY	130	170	130	160
GAS CONSUMPTION MJ/h	29	33	42	42
OUTPUT RATING -kW	5.8	6.6	10.5	10.5
RECOVERY RATE - NATURAL GAS LITRES PER HR 45°C RISE	110	126	200	200
LITRES AVAILABLE IN FIRST HOUR**	240	296	330	360

\*\* This is an industry standard calculated figure and should be used as a guide only.

LEGEND			
MP	MAINS PRESSURE	BCRL	BASE CIRCULATOR RISER LOOSE
LP	LOW PRESSURE	LHSC	LEFT HAND SIDE CIRCULATOR
VE	VITREOUS ENAMEL	RHSC	RIGHT HAND SIDE CIRCULATOR
UN	UNION	HHD	HEAVY HEAD (12.2M)
TWIN ELEMENT OPTION: WATER HEATER WIRED FOR SIMULTANEOUS ELEMENT OPERATION			

SAFE TRAYS	
417019	SAFE TRAY 660MM
417020	SAFE TRAY 800MM

## NOTES

---

---

---

---

---

---

---

---



### FULL TECH SUPPORT

Rheem has a national service and network of after sales professionals to provide expert technical advice and fast service.



### A TRUSTED BRAND

You can trust the Rheem brand to provide reliable products using high quality components.

All warranties listed in this reference guide are for single family premises in a domestic application. For Raypak and Rheem Commercial Warranty information call 0800 657 336.

Please check the specifications are current at the time of ordering or building to incorporate the appliance.

All information is current at the time of publication, (July 2018) but may change without notice.

**[www.rheem.co.nz](http://www.rheem.co.nz)**

Free Phone 0800 657 336

Free Fax 0800 657 337



Effective from July 2018

**INSTALL A RHEEM**